

JT REAR SEAT MOUNTING PANELS

Included Parts:

- Main panel
- Upper mounting bracket
- Lower mounting bracket
- 2x stainless M6 bolt, washers, nut

Tools Required:

- 10mm wrench
- T20 torx screwdriver
- T50 torx bit (jeep toolkit)
- 4mm hex key

1. Begin by removing the upper pillar screw using a 20 screwdriver.

2. Put upper mounting bracket in place, and re-install the trim screw. Screw should be snug and firm, do not overtighten.



3 (Hard Top). Using the T50 from your jeep toolkit, remove the front-most hard top bolt, then re-install with lower bracket installed in place. If your hard top comes off often, place the lower bracket between the hard top and the body.



3 (Soft Top). Put soft top down and remove rear corners.

- Using the bits from your jeep toolkit, loosen the bolts holding on the rear upper door surrounds, then light the rear surround upward to expose the lower body surround bolt.

- Remove the frontmost body surround bolt. Place lower bracket in between body and body surround, then reinstall bolt.

- Pop upper surround back in to place, then tighten upper bolts.

JT REAR SEAT MOUNTING PANELS



4. Using the supplied bolt, washers, and nut, loosely attach the main panel to the top mount. You can let it hang momentarily. Set up and loosely install the hardware at the bottom bracket as well.
5. Move the panel into your desired position, and using a 4mm allen key and 10mm wrench, tighten the top first, then bottom hardware.



6. Items can be attached to either the opening in the panel, or to the slotted opening using 6mm hardware.

