

KL CHEROKEE ROOF LIGHT BAR MOUNTS

1. Remove the small clips/covers on the roof rails with a small flat blade screwdriver. Be gentle, these are fragile. 2 covers per side.
2. Remove the front and rear Torx bolts (4 total per side) with a T30 Torx. Do **NOT** use an impact tool. Hand tools only to prevent stripping a rivet.
3. Once the bolts are removed, push roof rail forward and then lift to remove, exposing the roof rivet nuts. Set roof rail aside. Now is a good time to clean up the roof.
4. Place the brackets over the front rivet nut and then slide it rearward to lock it in place. The vertical portion of the mount should be closer to the center of the vehicle.
5. Once the bracket is locked in place, place the roof rail over the top of the bracket and rivet nuts. Slide the rail gently forward if needed to seat the rivet nuts in to the grooves in the rail, then pull the rail rearward to lock in to place. Ensure both front and rear sets of rivets are locked in.
6. Reinstall the Torx bolts loosely. Once again check that mounting bracket is moved fully rearward. Tighten bolts until snug with **hand tools**. Do not overtighten.
7. Now you are able to mount the light bar. Make sure to place the included rubber washers between the mounts and the light bar body.
8. Once light bar is mounted, double check all bolts are tight, and reinstall plastic covers on roof rails



Note: Mounts are designed to accommodate a 42" curved light bar. Other sizes may fit, but have not been tested